

Special Use Doors Technical Specifications					
Feature	Model				
	2004SSE	CB PVC	CB Stainless	CB Access	1822
Door Panel					
Edge Type	Rolled	Extruded Flat	Rolled	Rolled	Capped
Thickness	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-5/8"
Skin Type	24 ga. Stainless 304	PVC	24 ga. Stainless 304	26 ga. Steel	Steel, Aluminum, Fiberglass
Polyurethane Insulated Core	✓	Hollow-Ribbed	✓	✓	✓
Standard Panel Colors 1 side white other stainless OPTION	Stainless ✓	White	Stainless	White	White
Pre-Painted	✓			✓	✓
Pre-Hung	✓	✓	✓	✓	✓
Universal Swing	✓				✓
Thermally broken	Panel Only		✓		
Door Sweeps	Top & Bottom	Top & Bottom	Dual Contact		
No wood blocking	✓	✓	✓	✓	
Door Jamb					
Depth	3-1/2"	3" standard	3-1/2"	3-1/2"	1-7/8"
Extendable Frame		4-1/2" or 6-1/2"			
Material	Aluminum	PVC	16 ga. Stainless	Aluminum	Aluminum
Finish	Mill	White	Stainless	White	Mill
Frame Attaches to Sliding Door				✓	
Weathersealing	Pile Weatherstrip	Pile Weatherstrip	Dual Contact		Pile Weatherstrip
Adjustable Strike Plate	✓	✓	✓	✓	✓
Lockset Features					
Non-Collapsible Nylon Lockset Insert	✓		✓	✓	
Special Slender Interior Lockset				✓	
Stainless Steel Latch OPTION		✓			✓
2-1/8" Bore	✓	✓	✓	✓	✓
2-3/4" Backset	✓	✓	✓	✓	✓
Hinges					
4x4" Stainless NRP Hinges	✓	✓	✓	✓	✓
Door Size					
			Out-to-Out Dimensions		
2668				✓	
3060				✓	37-3/16" x 81-5/16"
3068	37-15/16" x 81-1/8"	38" x 82"	38-5/8" x 81-7/16"	✓	
3070	37-15/16" x 85-1/8"	38" x 86"	38-5/8" x 85-7/16"		
4068	47-15/16" x 81-1/8"		48-5/8" x 81-7/16"		49-3/16" x 81-5/16"
4070	47-15/16" x 85-1/8"		48-5/8" x 85-7/16"		
6068			74-15/16" x 81-7/16"		73-7/8" x 81-5/16"
6070			74-15/16" x 85-7/16"		
Options / Accessories					
Accessories Facotry Installed	✓	✓		✓	✓
Optional Nailing Flange	✓	✓			Integral Standard
Prep for Panic and Closer	✓	✓	✓		✓
Prep for Deadbolt	✓	✓	✓	✓	✓
Standard Window Lite Options	✓	✓	✓	✓	✓