



1600 Series Utility Grade Aluminum Frame Walk Doors

FEATURES:

- 1-3/8" polyurethane insulated door panel
- extruded aluminum frame with integral J-Channel
- Available in standard or carriage-house style configurations
- Available with paneled or crossbuck skin on exterior of door
- Available with optional window lites
- Can be configured with standard or specialty hardware
- Provides classic styling at an affordable price
- Ideal for sheds, out buildings, temporary structures and other types of low-traffic utility applications

1600 SERIES Utility Grade - Aluminum Frame Walk Doors



Rolled edge panel provides similar appearance to high-traffic entry doors.

Durable, low-maintenance design for low-traffic applications at an economical price.

Ideal for storage buildings, temporary structures and other utility applications.

Provides the look of higher end doors in a versatile low cost design.

1600 Utility Grade Aluminum Frame Walk Door Specs

SKIN TYPE: 26 Gauge steel

PANEL THICKNESS: 1-3/8"

PANEL TYPE: Rolled Edge Insulated

JAMB FINISH: White

HINGES: 4" x 4" Zinc-plated (carriage house optional)

Out-to-Out Dimensions

3060	36-1/16"	x	71-15/16"
3068	36-1/16"	x	79-15/16"
4060	46-1/16"	x	71-15/16"
4068	46-1/16"	x	79-15/16"
5060 (DBL)	54-9/16"	x	72-13/16"
6060 (DBL)	71-15/16"	x	71-15/16"



Division of National Material of Michigan Limited Partnership

555 Lawton Avenue, P.O. Box 835 | Beloit, Wisconsin 53512-0835
 p. 608.365.2161 | f. 608.365.4565 | Toll Free. 800.766.2825 | www.cnbhnp.com