



Handed unit - door swing must be specified.



FIRE RATED

AVAILABLE OPTIONS:

- Finished Casing Kit
- Prepped for Deadbolt
- Prepped for both panic and closer
- 5 - 1/2" to 6 - 1/2" adjustable jamb
- 6 - 1/2" to 7 - 1/2" adjustable jamb
- 7 - 1/2" to 8 - 1/2" adjustable jamb

FEATURES:

- 1 - 3/4" rolled edge all-steel panel
- 24 ga. white smooth pre-painted galvanized steel skin
- 18 ga. two-piece adjustable (4 - 1/2" to 5 - 1/2") steel jamb
- 4" x 10" composite lockset reinforcement
- Full perimeter weather strip/smoke gasket
- Stainless steel hinges
- Low-profile ADA handicap threshold
- Certified 90-minute fire rating (B) label

DOOR TYPE ACTUAL UNIT SIZE

3068	36 - 1/16" x 80 - 1/8"
3070	36 - 1/16" x 84 - 1/8"
3668	42 - 1/16" x 80 - 1/8"
3670	42 - 1/16" x 84 - 1/8"





Casing Kit Mounting



Casing Kit Corner Lock



Six-fin Weather Seal
Poly Foam Core



Base Jamb and Trim



Certified 90-minute
fire rating (B) label

Two-piece frame design allows the same system to be used in a variety of wall thicknesses with lower inventory costs (depth change is from the trim kit).

Optional casing kit can be applied to both sides of frame for a clean finished appearance on interior applications.

Frame design accommodates installation in finished or unfinished walls. The trim kit can be applied over drywall and finished with a casing kit or the trim can be installed directly to the stud with wall facing attached through pre-punched slots in the trim.

With a two-piece frame, cartoned door remains same dimensions regardless of frame depth – no special storage or handling requirements for deep frame applications.

2007 FR Certified Prefinished Door Specs
PANEL: Rolled edge 1 - 3/4" urethane core - 24 ga. steel skin
FRAME: Pre-painted 18 ga. steel adjustable, 4 - 1/2" - 5 - 1/2" standard
LOCKSET PREP: Composite lock block, standard 2 - 1/8" bore, 2 - 3/4" backset
DEADBOLT: Blocking is standard. Bore is optional.
HINGES: 4" x 4" stainless steel fixed pin
THRESHOLD: ADA Compliant fixed aluminum
WEATHER SEAL: Perimeter kerf compression seal with heavy duty six fin sweep
Handed unit - door swing must be specified.

