

Special Use STAINLESS STEEL DOOR CB • SS SERIES



FEATURES:

- Full thermal break of jambs, header/threshold and panel
- 16 Ga. x 3-1/2" stainless steel jambs with aluminum threshold
- 24 Ga. 304 or 316 stainless steel door panel
- Full perimeter weatherstripping
- 3'-0" x 6'-8" and 3'-0" x 7'-0" standard sizes, other sizes are available
- Nylon lockset insert eliminates lockset loosening. No wood block to deteriorate or absorb moisture.
- Stainless steel hinges
- Adjustable ss strike plate

Thermal break panel and frame provides:

- Excellent energy savings panels solid filled w/ urethane foam
- R-value = 12 plus
- Prepped for closures and panic bar

NON-COLLAPSIBLE NYLON LOCKSET INSERT



Door Type	Actual Unit Size
3' - 0" x 6' - 8"	38-5/8" x 81-7/16"
3' - 0" x 7' - 0"	38-5/8" x 85-7/16"
4' - 0" x 6' - 8"	48-5/8" x 81-7/16"
6' - 0" x 7' - 0"	48-5/8" x 85-7/16"



Handed unit - door swing must be specified!

OPTIONS:

- Stainless steel lockset

DUAL CONTACT THERMAL BREAK WEATHER SEAL



1-1/4" x 3-5/8" 16 Ga. Frame w/ Pre-Painted steel over hot dip galv.

Note: Standard jambs are not punched for fasteners - must specify mounting method at time of ordering.

SPECIAL USE